



Select 8

Copeland[™]
brand products



EMERSON



Project Report

Project Details: Sabacool.ir
Contact: 09128869515, Sarma Tajhiz Saba
Alborz Industrial City, Qazvin, Iran

Author Name: Sarma Tajhiz Saba (Sabacool)

Refrigerant	R22
High Side Properties:	
Condensing Temperature, °C	50.00
Abs. Condensing Pressure, bar	19.42
Dew Point, °C	50.00
Bubble Point, °C	50.00
Saturated vapour enthalpy, kJ/kg	718.00
Specific volume of saturated vapour, dm ³ /kg	11.70
Liquid Temperature, °C	50.00
Liquid enthalpy, kJ/kg	563.00
Low Side Properties:	
Evaporating Temperature, °C	20.00-
Evaporating Abs. Pressure, bar	2.45
Dew Point, °C	20.00-
Bubble Point, °C	20.00-
With vapour at, °C	10.00-
Specific volume, dm ³ /kg	97.50
Enthalpy, kJ/kg	704.00
Operating Conditions:	
Evaporating Temperature, °C	20.00-
Condensing Temperature, °C	50.00
Suction Superheat, K	10.00
Subcooling, K	0.00
Compressor Selected	6TA-1500

PERFORMANCE AT SPECIFIED OPERATING POINT
6TA-1500 Data at 50 Hz

Cooling Capacity, kW	20.90
Power, kW	13.75
COP	1.52
Current at 400 V, A	23.90
Suction Mass Flow, g/s	148.00
Heating Capacity, kW	34.00
Isentropic Eff., %	60.48

COMPRESSOR MECHANICAL AND PHYSICAL DATA

Number of cylinders	6
Displacement @ 50 Hz, m ³ /h	56.0
Bore/Stroke, mm	63.5/50.8
Length/Width, mm	755/585
Height, mm	575
Net Weight, kg	219
Gross Weight, kg	249
Suction, inch	1 5/8
Discharge, inch	1 3/8
Oil Quantity, l	3.3
Oil type (original charge)	POE RL32-3MAF
Oil type (approved oils)	POE RL32-3MAF, POE MOBIL EAL Arctic 22 CC
Base mounting (hole dia), mm	381 x 305 (18)
High Side PS gauge, bar	32.5
Low Side PS gauge, bar	22.5
Refrigerant's GWP	1810
Refrigerant's classification	A1

COMPRESSOR ELECTRICAL DATA (380-420 V / 3~ / 50 Hz)

Maximum Operating Current, A	30.1
Locked Rotor Current, A	174
Default Enclosure Class	IP 54 (IEC 34)

ACCESSORIES INCLUDED

Oil Pressure Switch	OPS2 Sensor
Mounting Springs	4

ACCESSORIES OPTIONAL

Enclosure Class	IP 56
Oil Pressure Switch	OPS2 Electronic Switch
Deep Oil Sump	Mounted
Adapter Kit	For Parallel Operation
Oil Control System	ALCO Trax-Oil OM3

D6TA, D6TH

