



Minimum Evaporating Temp. With:
█ 25 °C Suction Gas Return
█ Maximum Evaporating Temperature

Suction Return Temperature 20.0°C

Evaporating Temperature, °C

Liquid Subcooling 0.0K

Cond °C	Cooling Capacity, kW						
	50.0-	45.0-	40.0-	35.0-	30.0-	25.0-	20.0-
25.0	9.77	12.30	15.35	19.10	23.60	28.80	35.10
30.0	9.62	12.10	15.15	18.85	23.30	28.50	34.60
35.0	9.45	11.95	14.95	18.60	22.90	28.10	34.20
40.0	9.24	11.70	14.70	18.25	22.60	27.70	33.60
45.0	8.99	11.40	14.35	17.90	22.10	27.20	33.10
50.0		11.05	13.95	17.45	21.60	26.60	32.40
55.0		10.65	13.50	16.95	21.10	25.90	31.70

Cond °C	Power, kW						
	50.0-	45.0-	40.0-	35.0-	30.0-	25.0-	20.0-
25.0	7.83	8.64	9.49	10.40	11.30	12.20	13.10
30.0	8.25	9.13	10.10	11.05	12.10	13.15	14.20
35.0	8.67	9.63	10.65	11.80	12.95	14.15	15.40
40.0	9.08	10.15	11.30	12.55	13.85	15.20	16.60
45.0	9.47	10.60	11.90	13.30	14.75	16.30	17.90
50.0		11.10	12.50	14.05	15.70	17.40	19.20
55.0		11.55	13.10	14.80	16.60	18.55	20.60

Cond °C	Current at 400 V, A						
	50.0-	45.0-	40.0-	35.0-	30.0-	25.0-	20.0-
25.0	16.96	18.03	19.19	20.41	21.66	22.94	24.21
30.0	17.52	18.69	19.98	21.36	22.80	24.29	25.80
35.0	18.08	19.37	20.80	22.35	24.00	25.72	27.49
40.0	18.63	20.05	21.65	23.39	25.26	27.22	29.27
45.0	19.16	20.73	22.51	24.46	26.56	28.79	31.12
50.0		21.40	23.37	25.54	27.89	30.40	33.04
55.0		22.05	24.23	26.64	29.26	32.06	35.02

Cond °C	Mass Flow, g/s						
	50.0-	45.0-	40.0-	35.0-	30.0-	25.0-	20.0-
25.0	40.00	51.40	65.80	84.00	106.50	135.00	169.50
30.0	39.60	51.00	65.30	83.40	106.00	134.00	168.50
35.0	39.10	50.40	64.70	82.60	105.00	133.00	167.50
40.0	38.40	49.70	63.80	81.70	104.00	131.50	166.00
45.0	37.50	48.70	62.80	80.40	102.50	130.00	164.50
50.0		47.40	61.40	78.90	101.00	128.00	162.00
55.0		45.80	59.60	77.00	98.70	126.00	159.50

COMPRESSOR MECHANICAL AND PHYSICAL DATA

Number of cylinders	6
Displacement @ 50 Hz, m ³ /h	70.8
Bore/Stroke, mm	68.2/55.5
Length/Width, mm	755/585
Height, mm	575
Net Weight, kg	227
Gross Weight, kg	257
Suction, inch	1 5/8
Discharge, inch	1 3/8
Oil Quantity, l	3.3
Oil type (original charge)	POE RL32-3MAF
Oil type (approved oils)	POE RL32-3MAF, POE MOBIL EAL Arctic 22 CC
Base mounting (hole dia), mm	381 x 305 (18.0)
High Side PS, bar(g)	32.5
Low Side PS, bar(g)	22.5
Refrigerant's GWP	1810
Refrigerant's classification	A1

COMPRESSOR ELECTRICAL DATA (380-420 V / 3~ / 50 Hz)

Maximum Operating Current, A	36.3
Locked Rotor Current, A	173
Default Enclosure Class	IP 54 (IEC 34)

ACCESSORIES INCLUDED

Oil Pressure Switch	OPS2 Sensor
Mounting Springs	4
Liquid Subcooler	Plate Heat Exchanger

ACCESSORIES OPTIONAL

Enclosure Class	IP 56
Oil Pressure Switch	OPS2 Electronic Switch
Deep Oil Sump	Mounted
Adapter Kit	For Parallel Operation
Oil Control System	ALCO Trax-Oil OM3

MOTOR OPTIONS

Motor Code	Power Supply	Nominal Voltage, V	Start Connection	DOL Connection	Amps Factor
AWM	380-420 V / 3~ / 50 Hz	400	YYY	Y	1.00
EWL	220-240 V / 3~ / 50 Hz	230	Y/DELTA	DELTA	1.73
EWL	380-420 V / 3~ / 50 Hz	400		Y	1.00
EWM	380-420 V / 3~ / 50 Hz	400	Y/DELTA	DELTA	1.00
EWY	500-550 V / 3~ / 50 Hz	525	Y/DELTA	DELTA	0.76
AWR	220-240 V / 3~ / 50 Hz	230	YYY	Y	1.73
AWY	500-550 V / 3~ / 50 Hz	525	YYY	Y	0.76
TWY	500-550 V / 3~ / 50 Hz	525		DELTA	0.76
EWK	220-240 V / 3~ / 60 Hz	230	Y/DELTA	DELTA	2.10
EWK	380-420 V / 3~ / 60 Hz	380		Y	1.20
EWD	440-480 V / 3~ / 60 Hz	460	Y/DELTA	DELTA	1.00
AWC	208-230 V / 3~ / 60 Hz	230	YYY	Y	2.19
AWD	440-480 V / 3~ / 60 Hz	460	YYY	Y	1.00