



# Select 8

**Copeland**<sup>™</sup>  
brand products



**EMERSON**<sup>™</sup>



Project Report

Project Details: Sabacool.ir  
 Contact: 09128869515, Sarma Tajhiz Saba  
 Alborz Industrial City, Qazvin, Iran

Author Name: Sarma Tajhiz Saba (Sabacool)

Refrigerant	R404A Dew Point
<b>High Side Properties:</b>	
Condensing Temperature, °C	50.00
Abs. Condensing Pressure, bar	22.98
Dew Point, °C	50.00
Bubble Point, °C	49.70
Saturated vapour enthalpy, kJ/kg	382.00
Specific volume of saturated vapour, dm <sup>3</sup> /kg	7.30
Liquid Temperature, °C	49.70
Liquid enthalpy, kJ/kg	277.00
<b>Low Side Properties:</b>	
Evaporating Temperature, °C	20.00-
Evaporating Abs. Pressure, bar	3.03
Dew Point, °C	20.00-
Bubble Point, °C	20.60-
With vapour at, °C	10.00-
Specific volume, dm <sup>3</sup> /kg	67.90
Enthalpy, kJ/kg	364.00
<b>Operating Conditions:</b>	
Evaporating Temperature, °C	20.00-
Condensing Temperature, °C	50.00
Suction Superheat, K	10.00
Subcooling, K	0.00
Compressor Selected	D6TJ-250X

**PERFORMANCE AT SPECIFIED OPERATING POINT  
D6TJ-250X Data at 50 Hz**

Cooling Capacity, kW	23.70
Power, kW	24.10
COP	0.98
Current at 400 V, A	42.11
Suction Mass Flow, g/s	273.00
Heating Capacity, kW	46.60
Isentropic Eff., %	48.65

**COMPRESSOR MECHANICAL AND PHYSICAL DATA**

Number of cylinders	6
Displacement @ 50 Hz, m <sup>3</sup> /h	84.7
Bore/Stroke, mm	74.6/55.5
Length/Width, mm	755/585
Height, mm	630
Net Weight, kg	247
Gross Weight, kg	277
Suction, inch	1 5/8
Discharge, inch	1 3/8
Oil Quantity, l	6.8
Oil type (original charge)	POE RL32-3MAF
Oil type (approved oils)	POE RL32-3MAF, POE MOBIL EAL Arctic 22 CC
Base mounting (hole dia), mm	381 x 305 (18)
High Side PS gauge, bar	32.5
Low Side PS gauge, bar	22.5
Refrigerant's GWP	3922
Refrigerant's classification	A1

**COMPRESSOR ELECTRICAL DATA (380-420 V / 3~ / 50 Hz)**

Maximum Operating Current, A	40.2
Locked Rotor Current, A	203
Default Enclosure Class	IP 54 (IEC 34)

**ACCESSORIES INCLUDED**

Oil Pressure Switch	OPS2 Sensor
Mounting Springs	4
Deep Oil Sump	Mounted

**ACCESSORIES OPTIONAL**

Crankcase Heater	100 W Internal
Crankcase Heater	200 W Internal
Enclosure Class	IP 56
Oil Pressure Switch	OPS2 Electronic Switch
Adapter Kit	For Parallel Operation
Oil Control System	ALCO Trax-Oil OM3

# D6TJ

