



Select 8

Copeland[™]
brand products



EMERSON[™]



Project Report

Project Details: sabacool.ir
 Contact: 09128869515-Sarma Tajhiz Saba
 Alborz Industrial City, Qazvin, Iran

Author Name:

Refrigerant	R22
High Side Properties:	
Condensing Temperature, °C	50.00
Condensing Abs. Pressure, bar	19.42
Dew Point, °C	50.00
Bubble Point, °C	50.00
Saturated vapour enthalpy, kJ/kg	718.24
Specific volume of saturated vapour, dm ³ /kg	11.71
Liquid Temperature, °C	50.00
Liquid enthalpy, kJ/kg	563.07
Low Side Properties:	
Evaporating Temperature, °C	0.00
Evaporating Abs. Pressure, bar	4.97
Dew Point, °C	0.00
Bubble Point, °C	0.00
With vapour at, °C	20.00
Specific volume, dm ³ /kg	52.08
Enthalpy, kJ/kg	719.99
Operating Conditions:	
Evaporating Temperature, °C	0.00
Condensing Temperature, °C	50.00
Suction Return Temperature, °C	20.00
Subcooling, K	0.00
Compressor Selected	D2SA-45X Air

**PERFORMANCE AT SPECIFIED OPERATING POINT
D2SA-45X Air Data at 60Hz**

Error	Evap. pressure out of range
-------	-----------------------------

COMPRESSOR MECHANICAL AND PHYSICAL DATA

Number of cylinders	2
Displacement @ 60 Hz, m ³ /h	27
Bore/Stroke, mm	61.9/42.8
Length/Width, mm	560/330
Height, mm	395
Net Weight, kg	90
Gross Weight, kg	95
Suction, inch	1 1/8
Discharge, inch	7/8
Oil Quantity, l	2.4
Frequency Range, Hz	25 - 60
Oil type (original charge)	POE RL32-3MAF
Oil type (approved oils)	POE RL32-3MAF, POE MOBIL EAL Arctic 22 CC
Base mounting (hole dia), mm	295 x 279 (14.0)
High Side PS, bar(g)	32.5
Low Side PS, bar(g)	22.5
Refrigerant's GWP	1810
Refrigerant's classification	A1

COMPRESSOR ELECTRICAL DATA (380-420 V / 3~ / 60 Hz)

Maximum Operating Current, A	13.7
Locked Rotor Current, A	76.1
Default Enclosure Class	IP 54 (IEC 34)

ACCESSORIES INCLUDED

Oil Pressure Switch	OPS2 Sensor
Mounting Springs	4

ACCESSORIES OPTIONAL

Additional Cooling	70 W Vertical Air Flow Fan
Crankcase Heater	70 W Internal
Oil Pressure Switch	OPS2 Electronic Switch
Unloaded start	Available
Adapter Kit	For Parallel Operation
Check Valve	For unloaded start operation

D2S

