



Minimum Evaporating Temp. With:

- 25 °C Suction Gas Return
- 20 K suction Superheat
- Maximum Evaporating Temperature

Suction Return Temperature 20.0°C

Evaporating Temperature, °C

Liquid Subcooling 0.0K

Cond °C	Cooling Capacity, kW									
	25.0-	20.0-	15.0-	10.0-	5.0-	0.0	5.0	7.0	10.0	12.5
10.0	11.30	14.40	18.10	22.50	27.70					
15.0	10.55	13.50	17.10	21.30	26.30	32.00				
20.0	9.85	12.65	16.05	20.10	24.80	30.30	36.70	39.50		
25.0	9.16	11.85	15.05	18.90	23.40	28.70	34.80	37.50	41.80	45.70
30.0	8.50	11.05	14.10	17.70	22.00	27.00	32.80	35.40	39.50	43.20
35.0	7.86	10.25	13.15	16.55	20.60	25.40	30.90	33.30	37.30	40.80
40.0		9.50	12.20	15.45	19.30	23.80	29.00	31.30	35.10	38.40
45.0			11.30	14.35	17.95	22.20	27.10	29.30	32.90	36.00
50.0				13.30	16.70	20.70	25.30	27.40	30.70	33.70
55.0				12.30	15.45	19.15	23.50	25.50	28.60	31.40
60.0					14.25	17.70	21.80	23.60	26.50	29.10
62.0					13.80	17.15	21.10	22.80	25.70	28.20

Cond °C	Power, kW									
	25.0-	20.0-	15.0-	10.0-	5.0-	0.0	5.0	7.0	10.0	12.5
10.0	3.74	3.90	3.95	3.90	3.72					
15.0	3.94	4.16	4.30	4.35	4.27	4.06				
20.0	4.11	4.40	4.62	4.76	4.79	4.69	4.46	4.32		
25.0	4.25	4.61	4.91	5.14	5.27	5.29	5.19	5.10	4.93	4.75
30.0	4.37	4.79	5.17	5.49	5.73	5.86	5.88	5.86	5.77	5.66
35.0	4.46	4.96	5.42	5.82	6.16	6.41	6.56	6.58	6.58	6.54
40.0		5.10	5.64	6.13	6.57	6.93	7.20	7.28	7.36	7.40
45.0			5.84	6.42	6.96	7.44	7.83	7.96	8.13	8.23
50.0				6.70	7.34	7.92	8.44	8.62	8.87	9.05
55.0				6.96	7.70	8.39	9.03	9.27	9.60	9.84
60.0					8.05	8.85	9.61	9.90	10.30	10.65
62.0					8.18	9.03	9.84	10.15	10.60	10.95

Cond °C	Current at 400 V, A									
	25.0-	20.0-	15.0-	10.0-	5.0-	0.0	5.0	7.0	10.0	12.5
10.0	9.11	9.08	8.95	8.72	8.39					
15.0	9.34	9.46	9.48	9.40	9.22	8.93				
20.0	9.52	9.80	9.96	10.03	10.00	9.86	9.62	9.50		
25.0	9.67	10.08	10.40	10.62	10.73	10.74	10.65	10.59	10.46	10.33
30.0	9.76	10.33	10.79	11.16	11.42	11.58	11.64	11.63	11.60	11.54
35.0	9.81	10.53	11.14	11.65	12.06	12.37	12.58	12.63	12.68	12.70
40.0		10.68	11.44	12.10	12.66	13.11	13.47	13.58	13.72	13.81
45.0			11.69	12.50	13.21	13.81	14.32	14.49	14.72	14.88
50.0				12.86	13.71	14.47	15.12	15.35	15.67	15.91
55.0				13.17	14.17	15.07	15.87	16.17	16.57	16.88
60.0					14.59	15.64	16.58	16.94	17.43	17.82
62.0					14.74	15.85	16.86	17.23	17.76	18.18

Cond °C	Mass Flow, g/s									
	25.0-	20.0-	15.0-	10.0-	5.0-	0.0	5.0	7.0	10.0	12.5
10.0	53.00	67.80	85.70	107.00	132.50					
15.0	51.00	65.60	83.10	104.00	129.00	158.50				
20.0	49.00	63.30	80.50	101.00	126.00	155.00	189.00	204.00		
25.0	47.10	61.00	78.00	98.30	122.50	151.00	184.50	200.00	224.00	246.00
30.0	45.10	58.80	75.40	95.30	119.00	147.00	180.50	195.50	219.00	241.00
35.0	43.20	56.60	72.80	92.30	115.50	143.50	176.00	191.00	215.00	236.00
40.0		54.40	70.20	89.40	112.00	139.50	171.50	186.00	210.00	231.00
45.0			67.70	86.40	109.00	135.50	167.50	181.50	205.00	226.00
50.0				83.50	105.50	131.50	163.00	177.00	200.00	221.00
55.0				80.70	102.00	128.00	158.50	172.50	195.00	216.00
60.0					99.00	124.00	154.00	168.00	190.00	211.00
62.0					97.70	122.50	152.50	166.00	188.00	209.00

COMPRESSOR MECHANICAL AND PHYSICAL DATA

Number of cylinders	3
Displacement @ 50 Hz, m³/h	32.2
Bore/Stroke, mm	55.6/50.8
Length/Width, mm	655/370
Height, mm	480
Net Weight, kg	159
Gross Weight, kg	174
Suction, inch	1 3/8
Discharge, inch	1 1/8
Oil Quantity, l	3.7
Frequency Range, Hz	25 - 60
Oil type (original charge)	Suniso 3GS
Oil type (approved oils)	Suniso 3GS, TEXACO Capella WF 32, FUCHS Reniso KM
Base mounting (hole dia), mm	381 x 305 (18.0)
High Side PS, bar(g)	32.5
Low Side PS, bar(g)	22.5
Refrigerant's GWP	1810
Refrigerant's classification	A1

COMPRESSOR ELECTRICAL DATA (380-420 V / 3~ / 50 Hz)

Maximum Operating Current, A	18.5
Locked Rotor Current, A	83
Default Enclosure Class	IP 54 (IEC 34)

50Hz

D3SA-750

R22

ACCESSORIES INCLUDED

Oil Pressure Switch	OPS2 Sensor
Mounting Springs	4

ACCESSORIES OPTIONAL

Additional Cooling	70 W Vertical Air Flow Fan
Crankcase Heater	70 W Internal
Enclosure Class	IP 56
Oil Pressure Switch	OPS2 Electronic Switch
Unloaded start	Available
Deep Oil Sump	Mounted
Adapter Kit	For Parallel Operation
Check Valve	For unloaded start operation
Oil Control System	ALCO Trax-Oil OM3

MOTOR OPTIONS

Motor Code	Power Supply	Nominal Voltage, V	Start Connection	DOL Connection	Amps Factor
EWL	380-420 V / 3~ / 50 Hz	400		Y	1.00