



Minimum Evaporating Temp. With:

- 20 °C Suction Gas Return ASERCOM certified
- 0 °C Suction Gas Return
- ▨ K suction Superheat Limited superheat 20K
- Maximum Evaporating Temperature
- 25 °C Suction Gas Return
- 0 °C Suction Gas Return + fan
- | Voltage limit ± 5% above 20-°C

Suction Return Temperature 20.0°C

Evaporating Temperature, °C

Liquid Subcooling 0.0K

Cond °C	Cooling Capacity, kW								
	45.0-	40.0-	35.0-	30.0-	25.0-	20.0-	15.0-	10.0-	5.0-
10.0	10.00	13.60	18.10	23.60	30.30				
15.0	9.01	12.35	16.60	21.80	28.00	35.30			
20.0	8.13	11.25	15.20	20.00	25.80	32.60	40.50		
25.0		10.25	13.95	18.45	23.80	30.10	37.50	45.90	
30.0		9.33	12.75	16.90	21.90	27.70	34.60	42.40	51.30
35.0			11.60	15.45	20.00	25.40	31.70	39.00	47.20
40.0			10.45	13.95	18.20	23.10	28.90	35.60	43.20
45.0				12.50	16.35	20.90	26.10	32.20	39.20
50.0				11.00	14.50	18.60	23.40	28.90	35.20
55.0					12.55	16.25	20.50	25.50	31.20

Cond °C	Power, kW								
	45.0-	40.0-	35.0-	30.0-	25.0-	20.0-	15.0-	10.0-	5.0-
10.0	5.19	6.13	7.03	7.84	8.53				
15.0	5.24	6.24	7.22	8.14	8.95	9.61			
20.0	5.31	6.38	7.45	8.47	9.41	10.20	10.85		
25.0		6.51	7.68	8.82	9.89	10.85	11.65	12.30	
30.0		6.62	7.88	9.14	10.35	11.45	12.45	13.30	13.90
35.0			8.04	9.42	10.75	12.05	13.25	14.25	15.10
40.0			8.11	9.63	11.15	12.60	13.95	15.15	16.25
45.0				9.73	11.40	13.00	14.55	16.00	17.30
50.0				9.71	11.55	13.35	15.10	16.75	18.25
55.0					11.50	13.50	15.45	17.35	19.10

Cond °C	Current at 380 V, A								
	45.0-	40.0-	35.0-	30.0-	25.0-	20.0-	15.0-	10.0-	5.0-
10.0	11.49	12.37	13.30	14.21	15.02				
15.0	11.66	12.65	13.72	14.79	15.80	16.67			
20.0	11.78	12.87	14.07	15.31	16.52	17.63	18.57		
25.0		13.02	14.36	15.77	17.18	18.53	19.73	20.73	
30.0		13.10	14.58	16.16	17.78	19.36	20.83	22.13	23.18
35.0			14.72	16.48	18.30	20.12	21.86	23.46	24.85
40.0			14.78	16.71	18.74	20.80	22.82	24.72	26.44
45.0				16.86	19.10	21.40	23.69	25.90	27.96
50.0				16.91	19.36	21.91	24.48	27.00	29.40
55.0					19.53	22.32	25.17	28.00	30.74

Cond °C	Mass Flow, g/s								
	45.0-	40.0-	35.0-	30.0-	25.0-	20.0-	15.0-	10.0-	5.0-
10.0	55.60	75.60	101.00	132.50	170.50				
15.0	52.10	71.70	96.60	127.00	164.00	208.00			
20.0	49.20	68.30	92.50	122.50	158.50	201.00	251.00		
25.0		65.20	88.90	118.00	153.00	195.00	244.00	301.00	
30.0		62.30	85.40	114.00	148.00	188.50	237.00	293.00	358.00
35.0			82.00	109.50	143.00	183.00	230.00	285.00	349.00
40.0			78.50	105.50	138.00	177.00	223.00	277.00	340.00
45.0				101.00	132.50	170.50	215.00	268.00	330.00
50.0				95.60	126.50	164.00	208.00	260.00	321.00
55.0					120.00	156.00	199.50	251.00	311.00

COMPRESSOR MECHANICAL AND PHYSICAL DATA

Number of cylinders	4
Displacement @ 60 Hz, m ³ /h	67.6
Bore/Stroke, mm	63.5/50.8
Length/Width, mm	680/485
Height, mm	495
Net Weight, kg	178
Gross Weight, kg	194
Rotalock Discharge, inch	1 1/8
Suction, inch	1 5/8
Oil Quantity, l	3.3
Frequency Range, Hz	25 - 60
Oil type (original charge)	POE RL32-3MAF
Oil type (approved oils)	POE RL32-3MAF, POE MOBIL EAL Arctic 22 CC
Base mounting (hole dia), mm	381 x 305 (18.0)
Sound Pressure @ 1m (LT), dBA	74
Sound Pressure @ 1m (MT), dBA	72
Sound Power (LT), dBA	85
Sound Power (MT), dBA	83
High Side PS, bar(g)	32.5
Low Side PS, bar(g)	22.5
Refrigerant's GWP	3922
Refrigerant's classification	A1

COMPRESSOR ELECTRICAL DATA (380-420 V / 3~ / 60 Hz)

Maximum Operating Current, A	24.8
Locked Rotor Current, A	120
Default Enclosure Class	IP 54 (IEC 34)

ACCESSORIES INCLUDED

Oil Pressure Switch	OPS2 Sensor
Mounting Springs	4

ACCESSORIES OPTIONAL

Additional Cooling	70 W Vertical Air Flow Fan
Capacity Control	Capacity Steps 50%
Crankcase Heater	100 W Internal
Discharge Temperature Protection	Head PTC sensor
Enclosure Class	IP 56
Oil Pressure Switch	OPS2 Electronic Switch
Unloaded start	Available
Deep Oil Sump	Mounted
Adapter Kit	For Parallel Operation
Check Valve	For unloaded start operation
Oil Control System	ALCO Trax-Oil OM3
Inverter	Emerson Industrial Automation, Unidrive M200 06 400 420

MOTOR OPTIONS

Motor Code	Power Supply	Nominal Voltage, V	Start Connection	DOL Connection	Amps Factor
AWX	380 V / 3~ / 60 Hz	380	YYY	Y	1.00
EWL	220-240 V / 3~ / 50 Hz	230	Y/DELTA	DELTA	1.44
EWL	380-420 V / 3~ / 50 Hz	400		Y	0.83
EWM	380-420 V / 3~ / 50 Hz	400	Y/DELTA	DELTA	0.83
EWY	500-550 V / 3~ / 50 Hz	525	Y/DELTA	DELTA	0.63
AWR	220-240 V / 3~ / 50 Hz	230	YYY	Y	1.44
AWM	380-420 V / 3~ / 50 Hz	400	YYY	Y	0.83
AWY	500-550 V / 3~ / 50 Hz	525	YYY	Y	0.63
TWY	500-550 V / 3~ / 50 Hz	525		DELTA	0.63
EWK	220-240 V / 3~ / 60 Hz	230	Y/DELTA	DELTA	1.75
EWK	380-420 V / 3~ / 60 Hz	380		Y	1.00
EWD	440-480 V / 3~ / 60 Hz	460	Y/DELTA	DELTA	0.83
AWC	208-230 V / 3~ / 60 Hz	230	YYY	Y	1.82
AWD	440-480 V / 3~ / 60 Hz	460	YYY	Y	0.83