



Select 8

Copeland[™]
brand products



EMERSON



Project Report

Project Details: Sabacool.ir
 Contact: 09128869515, Sarma Tajhiz Saba
 Alborz Industrial City, Qazvin, Iran

Author Name: Sarma Tajhiz Saba (Sabacool)

Refrigerant	R22
High Side Properties:	
Condensing Temperature, °C	50.00
Abs. Condensing Pressure, bar	19.42
Dew Point, °C	50.00
Bubble Point, °C	50.00
Saturated vapour enthalpy, kJ/kg	718.00
Specific volume of saturated vapour, dm ³ /kg	11.70
Liquid Temperature, °C	50.00
Liquid enthalpy, kJ/kg	563.00
Low Side Properties:	
Evaporating Temperature, °C	20.00-
Evaporating Abs. Pressure, bar	2.45
Dew Point, °C	20.00-
Bubble Point, °C	20.00-
With vapour at, °C	10.00-
Specific volume, dm ³ /kg	97.50
Enthalpy, kJ/kg	704.00
Operating Conditions:	
Evaporating Temperature, °C	20.00-
Condensing Temperature, °C	50.00
Suction Superheat, K	10.00
Subcooling, K	0.00
Compressor Selected	D9TL-0760 SUB

**PERFORMANCE AT SPECIFIED OPERATING POINT
D9TL-0760 SUB Data at 50 Hz**

Error

Evap. pressure out of range

COMPRESSOR MECHANICAL AND PHYSICAL DATA

Number of cylinders	3
Displacement @ 50 Hz, m ³ /h	25.3
Bore/Stroke, mm	60.3/50.8
Length/Width, mm	655/385
Height, mm	540
Net Weight, kg	163
Gross Weight, kg	176
Suction, inch	1 3/8
Discharge, inch	7/8
Oil Quantity, l	3.6
Oil type (original charge)	POE RL32-3MAF
Oil type (approved oils)	POE RL32-3MAF, POE MOBIL EAL Arctic 22 CC
Base mounting (hole dia), mm	381 x 305 (18)
High Side PS gauge, bar	32.5
Low Side PS gauge, bar	22.5
Refrigerant's GWP	1810
Refrigerant's classification	A1

COMPRESSOR ELECTRICAL DATA (380-420 V / 3~ / 50 Hz)

Maximum Operating Current, A	16.8
Locked Rotor Current, A	78
Default Enclosure Class	IP 54 (IEC 34)

ACCESSORIES INCLUDED

Oil Pressure Switch	OPS2 Sensor
Mounting Springs	4
Liquid Subcooler	Plate Heat Exchanger

ACCESSORIES OPTIONAL

Oil Pressure Switch
Deep Oil Sump
Adapter Kit
Oil Control System

OPS2 Electronic Switch
Mounted
For Parallel Operation
ALCO Trax-Oil OM3

D9TK, D9TL, D9TH

