



# Select 8

**Copeland**<sup>™</sup>  
brand products



**EMERSON**<sup>™</sup>



## Project Report

Project Details: sabacool.ir  
Contact: 09128869515-Sarma Tajhiz Saba  
Alborz Industrial City, Qazvin, Iran

Author Name:

Refrigerant	R134a
<b>High Side Properties:</b>	
Condensing Temperature, °C	50.00
Condensing Abs. Pressure, bar	13.17
Dew Point, °C	50.00
Bubble Point, °C	50.00
Saturated vapour enthalpy, kJ/kg	424.30
Specific volume of saturated vapour, dm <sup>3</sup> /kg	15.10
Liquid Temperature, °C	50.00
Liquid enthalpy, kJ/kg	272.48
<b>Low Side Properties:</b>	
Evaporating Temperature, °C	0.00
Evaporating Abs. Pressure, bar	2.93
Dew Point, °C	0.00
Bubble Point, °C	0.00
With vapour at, °C	20.00
Specific volume, dm <sup>3</sup> /kg	76.17
Enthalpy, kJ/kg	416.59
<b>Operating Conditions:</b>	
Evaporating Temperature, °C	0.00
Condensing Temperature, °C	50.00
Suction Return Temperature, °C	20.00
Subcooling, K	0.00
Compressor Selected	DLJ-20X

**PERFORMANCE AT SPECIFIED OPERATING POINT  
DLJ-20X Data at 50Hz**

Cooling Capacity, kW	5.66
Power, kW	2.50
COP	2.26
Current at 400 V, A	4.92
Mass Flow, g/s	39.30
Heat Rejection, kW	7.02
Isentropic Eff., %	54.38

**COMPRESSOR MECHANICAL AND PHYSICAL DATA**

Number of cylinders	2
Displacement @ 50 Hz, m <sup>3</sup> /h	14.5
Bore/Stroke, mm	54.0/36.5
Length/Width, mm	470/330
Height, mm	385
Net Weight, kg	78
Gross Weight, kg	84
Suction, inch	7/8
Discharge, inch	5/8
Oil Quantity, l	2
Frequency Range, Hz	25 - 60
Oil type (original charge)	POE RL32-3MAF
Oil type (approved oils)	POE RL32-3MAF, POE MOBIL EAL Arctic 22 CC
Base mounting (hole dia), mm	295 x 279 (14.0)
Sound Pressure @ 1m, dBA	52
Sound Power, dBA	63
High Side PS, bar(g)	32.5
Low Side PS, bar(g)	22.5
Refrigerant's GWP	1430
Refrigerant's classification	A1

**COMPRESSOR ELECTRICAL DATA (380-420 V / 3~ / 50 Hz)**

Maximum Operating Current, A	5.6
Locked Rotor Current, A	37.6
Default Enclosure Class	IP 54 (IEC 34)

**ACCESSORIES INCLUDED**

Mounting Springs	4
------------------	---

**ACCESSORIES OPTIONAL**

Additional Cooling	1 or 2 ways water Coil
Additional Cooling	70 W Vertical Air Flow Fan
Additional Cooling	25 W Horizontal Air Flow Fan
Crankcase Heater	70 W Internal
Adapter Kit	For Parallel Operation
Oil Control System	ALCO Trax-Oil OM3
Inverter	Emerson Industrial Automation, Unidrive M200 03 400 094

DL with pump

