



Select 8

Copeland[™]
brand products



EMERSON[™]



Project Report

Project Details: sabacool.ir
 Contact: 09128869515-Sarma Tajhiz Saba
 Alborz Industrial City, Qazvin, Iran

Author Name:

Refrigerant	R404A Dew Point
High Side Properties:	
Condensing Temperature, °C	50.00
Condensing Abs. Pressure, bar	22.98
Dew Point, °C	50.00
Bubble Point, °C	49.70
Saturated vapour enthalpy, kJ/kg	381.56
Specific volume of saturated vapour, dm ³ /kg	7.29
Liquid Temperature, °C	49.70
Liquid enthalpy, kJ/kg	276.83
Low Side Properties:	
Evaporating Temperature, °C	0.00
Evaporating Abs. Pressure, bar	6.04
Dew Point, °C	0.00
Bubble Point, °C	0.54-
With vapour at, °C	20.00
Specific volume, dm ³ /kg	36.66
Enthalpy, kJ/kg	384.92
Operating Conditions:	
Evaporating Temperature, °C	0.00
Condensing Temperature, °C	50.00
Suction Return Temperature, °C	20.00
Subcooling, K	0.00
Compressor Selected	DLL-30X

**PERFORMANCE AT SPECIFIED OPERATING POINT
DLL-30X Data at 50Hz**

Error Evap. pressure out of range

COMPRESSOR MECHANICAL AND PHYSICAL DATA

Number of cylinders	2
Displacement @ 50 Hz, m ³ /h	18.2
Bore/Stroke, mm	60.4/36.5
Length/Width, mm	470/330
Height, mm	385
Net Weight, kg	85
Gross Weight, kg	91
Suction, inch	1 1/8
Discharge, inch	5/8
Oil Quantity, l	2
Frequency Range, Hz	25 - 60
Oil type (original charge)	POE RL32-3MAF
Oil type (approved oils)	POE RL32-3MAF, POE MOBIL EAL Arctic 22 CC
Base mounting (hole dia), mm	295 x 279 (14.0)
Sound Pressure @ 1m, dBA	52
Sound Power, dBA	63
High Side PS, bar(g)	32.5
Low Side PS, bar(g)	22.5
Refrigerant's GWP	3922
Refrigerant's classification	A1

COMPRESSOR ELECTRICAL DATA (380-420 V / 3~ / 50 Hz)

Maximum Operating Current, A	7.3
Locked Rotor Current, A	53
Default Enclosure Class	IP 54 (IEC 34)

ACCESSORIES INCLUDED

Mounting Springs	4
------------------	---

ACCESSORIES OPTIONAL

Additional Cooling	1 or 2 ways water Coil
Additional Cooling	70 W Vertical Air Flow Fan
Additional Cooling	25 W Horizontal Air Flow Fan
Crankcase Heater	70 W Internal
Adapter Kit	For Parallel Operation
Oil Control System	ALCO Trax-Oil OM3
Inverter	Emerson Industrial Automation, Unidrive M200 04 400 135

DL with pump

