



# Select 8

**Copeland**<sup>™</sup>  
brand products



**EMERSON**<sup>™</sup>



**Project Report**

Project Details: sabacool.ir  
 Contact: 09128869515-Sarma Tajhiz Saba  
 Alborz Industrial City, Qazvin, Iran

Author Name:

Refrigerant	R22
<b>High Side Properties:</b>	
Condensing Temperature, °C	50.00
Condensing Abs. Pressure, bar	19.42
Dew Point, °C	50.00
Bubble Point, °C	50.00
Saturated vapour enthalpy, kJ/kg	718.24
Specific volume of saturated vapour, dm³/kg	11.71
Liquid Temperature, °C	50.00
Liquid enthalpy, kJ/kg	563.07
<b>Low Side Properties:</b>	
Evaporating Temperature, °C	0.00
Evaporating Abs. Pressure, bar	4.97
Dew Point, °C	0.00
Bubble Point, °C	0.00
With vapour at, °C	20.00
Specific volume, dm³/kg	52.08
Enthalpy, kJ/kg	719.99
<b>Operating Conditions:</b>	
Evaporating Temperature, °C	0.00
Condensing Temperature, °C	50.00
Suction Return Temperature, °C	20.00
Subcooling, K	0.00
Compressor Selected	DLL-401

**PERFORMANCE AT SPECIFIED OPERATING POINT  
DLL-401 Data at 50Hz**

Cooling Capacity, kW	12.60
Power, kW	4.69
COP	2.68
Current at 400 V, A	7.91
Mass Flow, g/s	80.20
Heat Rejection, kW	15.60
Isentropic Eff., %	64.99

**COMPRESSOR MECHANICAL AND PHYSICAL DATA**

Number of cylinders	2
Displacement @ 50 Hz, m <sup>3</sup> /h	18.2
Bore/Stroke, mm	60.4/36.5
Length/Width, mm	460/330
Height, mm	385
Net Weight, kg	87
Gross Weight, kg	93
Suction, inch	1 1/8
Discharge, inch	5/8
Oil Quantity, l	2
Frequency Range, Hz	25 - 60
Oil type (original charge)	Suniso 3GS
Oil type (approved oils)	Suniso 3GS, TEXACO Capella WF 32, FUCHS Reniso KM
Base mounting (hole dia), mm	295 x 279 (14.0)
Sound Pressure @ 1m, dBA	62.6
Sound Power, dBA	73.6
High Side PS, bar(g)	32.5
Low Side PS, bar(g)	22.5
Refrigerant's GWP	1810
Refrigerant's classification	A1

**COMPRESSOR ELECTRICAL DATA (380-420 V / 3~ / 50 Hz)**

Maximum Operating Current, A	9.9
Locked Rotor Current, A	58.9
Default Enclosure Class	IP 54 (IEC 34)

**ACCESSORIES INCLUDED**

Mounting Springs	4
------------------	---

**ACCESSORIES OPTIONAL**

Additional Cooling	1 or 2 ways water Coil
Additional Cooling	70 W Vertical Air Flow Fan
Additional Cooling	25 W Horizontal Air Flow Fan
Crankcase Heater	70 W Internal
Adapter Kit	For Parallel Operation
Oil Control System	ALCO Trax-Oil OM3

# DL without oil pump

