



Select 8

Copeland[™]
brand products



EMERSON[™]



Project Report

Project Details: sabacool.ir
 Contact: 09128869515-Sarma Tajhiz Saba
 Alborz Industrial City, Qazvin, Iran

Author Name:

Refrigerant	R134a
High Side Properties:	
Condensing Temperature, °C	50.00
Condensing Abs. Pressure, bar	13.17
Dew Point, °C	50.00
Bubble Point, °C	50.00
Saturated vapour enthalpy, kJ/kg	424.30
Specific volume of saturated vapour, dm ³ /kg	15.10
Liquid Temperature, °C	50.00
Liquid enthalpy, kJ/kg	272.48
Low Side Properties:	
Evaporating Temperature, °C	0.00
Evaporating Abs. Pressure, bar	2.93
Dew Point, °C	0.00
Bubble Point, °C	0.00
With vapour at, °C	20.00
Specific volume, dm ³ /kg	76.17
Enthalpy, kJ/kg	416.59
Operating Conditions:	
Evaporating Temperature, °C	0.00
Condensing Temperature, °C	50.00
Suction Return Temperature, °C	20.00
Subcooling, K	0.00
Compressor Selected	DLSG-40X

**PERFORMANCE AT SPECIFIED OPERATING POINT
DLSG-40X Data at 50Hz**

Cooling Capacity, kW	9.59
Power, kW	3.81
COP	2.52
Current at 400 V, A	6.96
Mass Flow, g/s	66.50
Heat Rejection, kW	11.90
Isentropic Eff., %	60.44

COMPRESSOR MECHANICAL AND PHYSICAL DATA

Number of cylinders	2
Displacement @ 50 Hz, m ³ /h	22.5
Bore/Stroke, mm	61.9/42.8
Length/Width, mm	470/330
Height, mm	385
Net Weight, kg	77
Gross Weight, kg	82
Suction, inch	1 1/8
Discharge, inch	5/8
Oil Quantity, l	2
Frequency Range, Hz	25 - 60
Oil type (original charge)	POE RL32-3MAF
Oil type (approved oils)	POE RL32-3MAF, POE MOBIL EAL Arctic 22 CC
Base mounting (hole dia), mm	295 x 279 (14.0)
Sound Pressure @ 1m, dBA	63
Sound Power, dBA	74
High Side PS, bar(g)	28
Low Side PS, bar(g)	22.5
Refrigerant's GWP	1430
Refrigerant's classification	A1

COMPRESSOR ELECTRICAL DATA (380-420 V / 3~ / 50 Hz)

Maximum Operating Current, A	8.5
Locked Rotor Current, A	68.5
Default Enclosure Class	IP 54 (IEC 34)

ACCESSORIES INCLUDED

Mounting Springs	4
------------------	---

ACCESSORIES OPTIONAL

Additional Cooling	1 or 2 ways water Coil
Additional Cooling	70 W Vertical Air Flow Fan
Additional Cooling	25 W Horizontal Air Flow Fan
Crankcase Heater	70 W Internal
Adapter Kit	For Parallel Operation

DL with pump

