



Select 8

Copeland[™]
brand products



EMERSON[™]



Project Report

Project Details: sabacool.ir
 Contact: 09128869515-Sarma Tajhiz Saba
 Alborz Industrial City, Qazvin, Iran

Author Name:

Refrigerant	R22
High Side Properties:	
Condensing Temperature, °C	50.00
Condensing Abs. Pressure, bar	19.42
Dew Point, °C	50.00
Bubble Point, °C	50.00
Saturated vapour enthalpy, kJ/kg	718.24
Specific volume of saturated vapour, dm ³ /kg	11.71
Liquid Temperature, °C	50.00
Liquid enthalpy, kJ/kg	563.07
Low Side Properties:	
Evaporating Temperature, °C	0.00
Evaporating Abs. Pressure, bar	4.97
Dew Point, °C	0.00
Bubble Point, °C	0.00
With vapour at, °C	20.00
Specific volume, dm ³ /kg	52.08
Enthalpy, kJ/kg	719.99
Operating Conditions:	
Evaporating Temperature, °C	0.00
Condensing Temperature, °C	50.00
Suction Return Temperature, °C	20.00
Subcooling, K	0.00
Compressor Selected	KM-50

**PERFORMANCE AT SPECIFIED OPERATING POINT
KM-50 Data at 60Hz**

Error	Evap. pressure out of range
-------	-----------------------------

COMPRESSOR MECHANICAL AND PHYSICAL DATA

Number of cylinders	2
Displacement @ 60 Hz, m ³ /h	4.79
Bore/Stroke, mm	34.9/23.8
Length/Width, mm	355/235
Height, mm	280
Net Weight, kg	39
Gross Weight, kg	41
Suction, inch	1/2
Discharge, inch	1/2
Oil Quantity, l	0.65
Frequency Range, Hz	25 - 60
Oil type (original charge)	Suniso 3GS
Oil type (approved oils)	Suniso 3GS, TEXACO Capella WF 32, FUCHS Reniso KM
Base mounting (hole dia), mm	208 x 162 (11.0)
High Side PS, bar(g)	32.5
Low Side PS, bar(g)	22.5
Refrigerant's GWP	1810
Refrigerant's classification	A1

COMPRESSOR ELECTRICAL DATA (380-420 V / 3~ / 60 Hz)

Default Enclosure Class	IP 54 (IEC 34)
-------------------------	----------------

ACCESSORIES INCLUDED

Mounting Springs	4
------------------	---

ACCESSORIES OPTIONAL

Additional Cooling	1 or 2 ways water Coil
Additional Cooling	25 W Horizontal Air Flow Fan
Additional Cooling	7 W Vertical Air Flow Fan
Crankcase Heater	27 W Internal
Adapter Kit	For Parallel Operation
Oil Control System	ALCO Trax-Oil OM3

DK without oil pump

